

# NetKey® Category 5e Leadframe Jack Modules

## specifications

Category 5e/Class D, 8-position keystone UTP jack module shall terminate unshielded twisted 4-pair, 24 – 22 AWG, 100 ohm cable without the use of a punchdown tool. Optional tool ensures conductors are fully terminated. Universal label is color-coded T568A and T568B wiring schemes.



## technical information

<b>Category 5e/Class D channel and component performance:</b>	Exceeds channel requirements of ANSI/TIA-568.2-D Category 5e and ISO 11801 Class D standards at swept frequencies 1 to 100 MHz Exceeds component requirements of ANSI/TIA-568.2-D Category 5e and ISO 11801 Class D standards at swept frequencies 1 to 100 MHz
<b>FCC and ANSI compliance:</b>	Meets ANSI/TIA-1096-A; contacts plated with 50 microinches of gold for superior performance
<b>IEC compliance:</b>	Meets IEC 60603-7 and IEC 60512-99-002
<b>PoE and PoH compliance:</b>	Meets IEEE 802.3af/802.3at and 802.3bt type 3 and type 4. Supports Power over HDBaseT up to 100 watts
<b>c(UL)us listed:</b>	UL 1863 (Use as communications circuit accessory); CSA standard C22.2
<b>RoHS compliance:</b>	Compliant
<b>Operating temperature:</b>	-10°C to 60°C (14°F to 140°F)

## key features and benefits

<b>100% performance tested</b>	Confidence that each jack module delivers specified performance
<b>Termination cap</b>	Provides strain relief, helps control cable end radius and securely retains wires in place
<b>Modular</b>	Universal keystone jack modules snap in and out of all NetKey Faceplates, Modular Patch Panels, and Surface Mount Boxes for fast moves, adds, and changes
<b>Bulk packaging (optional)</b>	25 jacks packaged in one easy to open container, eliminating the time to open each individual package and reducing on-site waste; ideal for high volume installations

## applications

Applications include:

- Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), and 1000BASE-T (Gigabit Ethernet)
- Voice over internet protocol (VoIP)

### NetKey Category 5e Jack Modules

**Module:** NK5E88M\*Y

**Bulk pack of 25 modules:** NK5E88M\*-Q

### NetKey Category 5e Patch Cords

**24-port, 1 RU:** NKFP24Y

**48-port, 2 RU:** NKFP48Y

### Termination Tools

**Termination tool:** CJT‡



**Snipping tool:** CWST

**Stripping tool:** CJUST

\*To designate a color, add suffix IW (Off White), EI (Electric Ivory), IG (Int'l Gray), WH (White), BL (Black), OR (Orange), RD (Red), BU (Blue), GR (Green), VL (Violet), AW (Arctic White), or YL (Yellow).

‡Terminates NetKey Keystone Leadframe Jack Modules.

# NetKey® Category 5e Leadframe Jack Modules



Dimensions are in inches. [Dimensions in brackets are metric].

## WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)  
Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300

**PANDUIT**®

© 2022 Panduit Corp.  
ALL RIGHTS RESERVED.  
NKDS32--WW-ENG  
9/2022